



Note 1: Suggested Maximum Torque: 28.25 N-cm
While this value is provided from reliable sources, there are many variables that will effect this value and the use of this information is at the sole risk of the user.

TITLE: DOC00734 Rev-C MS-IMU3025 Dimensional Drawing Metric			
UNLESS OTHERWISE SPECIFIED:		NAME	DATE
DIMENSIONS ARE IN MM		DRAWN	JB 07-29-2020
TOLERANCES		ENG APPR.	DL 07-29-2020
ANGULAR: MACH ±0.1		MFG APPR.	EL 07-29-2020
TWO PLACE DECIMAL ±0.25		DOC NO	
THREE PLACE DECIMAL ±0.076		DOC00734	
FOUR PLACE DECIMAL ±0.0127		REV	
INTERPRET GEOMETRIC TOLERANCING PER: ASME Y14.5-2009		C	
MATERIAL	6061-T6 AL	SIZE	PART NO
FINISH	MIL-A-8625 ANODIZE	A	MP00075
DO NOT SCALE DRAWING		SCALE: 2:1	WEIGHT:
		SHEET 1 OF 1	



PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MEMSENSE, LLC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF MEMSENSE, LLC IS PROHIBITED.