



**Note 1: Suggested Maximum Torque: 28.2 N-cm**  
 This value is a maximum, it is not recommended to torque to this value. While this value is provided from reliable sources, there are many variables that may effect this value and the use of this information is at the sole risk of the user.

TITLE: DOC00466 Rev-D MS-IMU3050 Dimensional Drawing Metric			
UNLESS OTHERWISE SPECIFIED:		NAME	DATE
DIMENSIONS ARE IN MM		DRAWN	JB
TOLERANCES		EFFECTIVE	PLM
ANGULAR: MACH $\pm 0.1$			
TWO PLACE DECIMAL $\pm 0.254$			
THREE PLACE DECIMAL $\pm 0.0762$			
FOUR PLACE DECIMAL $\pm 0.0127$			
INTERPRET GEOMETRIC TOLERANCING PER: ASME Y14.5-2018		DOC NO	REV
		DOC00466	D
MATERIAL	6061-T6 ALUMINUM	SIZE	PART NO
FINISH	MIL-A-8625 ANODIZE	<b>A</b>	MP00067
DO NOT SCALE DRAWING		SCALE: 1:1	WEIGHT: 79g
		SHEET 1 OF 1	



**PROPRIETARY AND CONFIDENTIAL**  
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MEMSENSE, LLC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF MEMSENSE, LLC IS PROHIBITED.